



## Specification of Grille light BL-GL-5x1W/3W- SemiLED/ XRE

### Product Images



Product Size: 190 x 190x125mm

Cut-out Size: 155x155mm

### Application

- \* Landscape accent spotlighting, display case accent lighting.
- \* Artworok lighting, mood lighting, shop windows, general lighting.
- \* Hotel, office, cafe or other architectural lighting.

### Product Highlights

- \* Easy installation: Standard fitting size, Plug-in replacement of current traditional lamps.
- \* Dimmable: Compatible with Triac dimmers on market such as Lutron, Leviton, legrand, Osram, and GE etc. dimming range is from 5~100% and very stable.
- \* Outstanding Performance: High lumen output, Effiecent > 80% , PF > 0.9, Life Span > 50,000 hours.



# Bravoled Lighting Manufacturing Co. Ltd.

## Specification

- \* Product Number: BL-GL-5x1W- SemiLED/ XRE  
BL-GL-5x3W- SemiLED/ XRE
- \* Description: High Power LED Grille Light 5x1W and 5x3W
- \* LED Chip Q'ty: 5 LED x 1W/3W
- \* LED Type: High power LED SemiLED/ CREE XRE
- \* Housing Material: Aluminum Alloy
- \* Housing Color: White/ Aluminum
- \* Driver: External
- \* Dimmability: working with PMW dimmers on market, not particularly for LED light.
- \* Input Voltage: 85-145V AC or 190-265V AC
- \* Input Power: 6.7Watt (5x1W) , 12.5Watt (5x3W)
- \* Output Power: 5.4Watt (5x1W), 10.0Watt (5x3W)
- \* Output Voltage: 16.0~17.0 V DC
- \* Output Current: 320mA (5x1W), 600mA (5x3W)
- \* Dimension: 190x190x125mm
- \* Cut-out Size: 155x155mm
- \* Weight: 700g
- \* Lumen Output : (5x1W) WW 360lm CW 470lm  
(5x3W) WW 535lm CW 705lm
- \* Color Temperature: Warm White: 2,700 ~3,500K, Cool White: 5,000~6,500K
- \* CRI: Ra> 80
- \* Power Factor: 0.9
- \* Lense Angle: 15/30/45/60 degrees
- \* Reflector Efficiency: 90%
- \* Life Span: >50,000 hours
- \* Warranty: 2 years
- \* Body Temperature: <65°C
- \* LED Working Temperature: <72°C
- \* NO UV OR IR RADIATION
- \* Certification: CE & Rohs

## Packing Specification

Carton Dimension 210x210x145mm, Pack Size : 1pc.